
Mutina

Renga ^{by} Vincent Van Duysen



ΕN


General information Laying and maintenance tips Colors Technical features Packing





General information

The data, information and indications contained in this technical data sheet and in further documents relating to the Renga by Vincent Van Duysen product are the exclusive property by Ceramiche MUTINA S.p.a. This Technical Data Sheet provides the buyer with information relating to the use of the product useful for its correct installation and evaluation and prevention of risks arising from the normal use of the same.


collection	Renga
design	Vincent Van Duysen, 2022
production	Artisanal
material	Glazed casting terracotta
nominal sizes	15xh25x15 cm (6"x10"x6")
specification	 3 colors: Ivory, Grey, Brown Non structural artisanal partition elements These elements must comply with the technical standards of construction regulation, applicable in the country where they are installed. For the Italian national territory, in particular, they should comply with standard NTC 2018 DECRETO MIN 27/01. The product is suitable for indoor and outdoor areas complying with UNI EN 772-22 marked "F1-moderate exposure"









laying scheme







laying scheme 2 28,19 pcs / sqm



laying scheme 3 28,19 pcs / sqm

Laying and maintenance tips

use	Wall – indoor, outdoor.					
installation	Insert a 50 mm wide "Murfor Compact" type reinforcing metal mesh between each horizontal row and along the entire length of the wall.					
recommended adhesive	Solvents-free, eco-friendly organic adhesive produced by Kerakoll in exclusive for Mutina.					
cleaning at the end of installation	Avoid drippings during installation. If needed the excess can be removed after the product has dried using a tool with a sharp edge.					
general cleaning (installed tiles)	-					
calibers (real size)	15 x 25 x 15 with a tolerance of 2 mm (artisanal product)					

Colors







Brown

Technical features

Non structural artisanal partition elements. These elements must in any case comply with the technical standards of construction regulation, applicable in the country where they are installed. For the Italian national territory, in particular, they should comply with standard NTC 2018 DECRETO MIN 27/01. This product is suitable for indoor and outdoor areas complying with UNI EN 722-22 marked "F1-moderate exposure"

STANDARD	FEATURES	VALUE REQUIRED	RENGA	
UNI EN 772-16	dimensions	to declare	T2-R2	
UNI EN 772-21:2011	water absorption	to declare	0,5%	
UNI EN 772-5:2016	content of active soluble salts	to declare	SO	
UNI EN CEN/TS 772- 22:2006	freeze-thaw resistance	to declare	F1	
D.M. 1401/2008	M. 1401/2008 determination of variable horizontal loads		C2	
VOC Emission				
Declaration of Contents				
SDS				

Packing

SIZE	PCS-SQM	PCS-BOX	SQM-PAL	BOX-PAL	KG-PC	KG-PAL
15·25·15 cm	see laying scheme	2	4,275	57	8.30	473,10

