

***DECLARATION OF CONFORMITY***  
***N° DoC-F***  
***Rev.0 – 25/11/2022***

1. Unique identification code of the product type:  
**DRY- PRESSED CERAMIC TILES, WITH WATER ABSORPTION  $E_b \leq 0,5\%$**
2. Intended uses:  
**FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS**
3. Name and contact address of the manufacturer:  
**EMILCERAMICA S.r.l. a socio unico**  
**Via GHIAROLA NUOVA, 29 41042 FIORANO M.SE (MO) ITALY**  
**Tel. : +39 0536 835111**  
[contact@emilceramicagroup.it](mailto:contact@emilceramicagroup.it)    [www.emilgroup.it](http://www.emilgroup.it)
4. System of AVCP: **SYSTEM 4**
5. Name and identification number of notified laboratory: **NOT APPLICABLE**
6. Declared Performances:

| Essential characteristics                                                      | Performance                                                                                                  | Designated technical specification |
|--------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|------------------------------------|
| Reaction to fire                                                               | Class A1 <sub>FL</sub> /A1                                                                                   | EN 14411:2012                      |
| Breaking strength                                                              | Thickness < 7,5 mm Breaking strength $\geq 700$ N<br>Thickness $\geq 7,5$ mm Breaking strength $\geq 1300$ N |                                    |
| Slipperiness                                                                   | NPD                                                                                                          |                                    |
| Tactility                                                                      | NPD                                                                                                          |                                    |
| Bond strength/adhesion                                                         | NPD                                                                                                          |                                    |
| Durability, for:<br>- Internal use<br>- External use: Freeze/thaw resistance   | Pass<br>Pass                                                                                                 |                                    |
| Resistance to thermal shock                                                    | Pass                                                                                                         |                                    |
| Release of dangerous substances, for:<br>Release of lead<br>Release of cadmium | NPD<br>NPD                                                                                                   |                                    |

*The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:*

Fiorano, 25/11/2022

Luca Gatti  
President

